

ZEROVAC LRV-340 / LRV-380

Monoblock Liquid Ring Vacuum Pumps



■ ROBUST

- Proven technology
- Corrosion-free stainless steel impeller
- High particle and vapor tolerance

■ COMPACT

- Directly flanged motor
- No base frame required
- Compact design, maximum performance

■ FLEXIBLE

- Cast iron, 304 or 316 grade stainless steel housing options
- ATEX-certified version available
- Operating fluids other than water possible

Accessories


- Partial or total recirculation systems
- Heat exchanger
- Non-return valves
- Liquid separator
- Gas ejector
- Vacuum relief valves
- Cavitation protection
- Wide selection of motors
- Different operating fluids possible

ZEROVAC LRV-340 / LRV-380


Monoblock Liquid Ring Vacuum Pumps



Installation Drawing



Performance Curve



Technical Data

50 / 60 Hz

	ZEROVAC LRV-340	ZEROVAC LRV-380
Nominal pumping speed	280 / 330 m³/h (50 / 60 Hz)	375 / 455 m³/h (50 / 60 Hz)
Ultimate Pressure	33 mbar (50 / 60 Hz)	33 mbar (50 / 60 Hz)
Negative Pressure	-735 mmHg (50 / 60 Hz)	-735 mmHg (50 / 60 Hz)
Motor Power	7.5 / 11 kW (50 / 60 Hz)	11 / 15 kW (50 / 60 Hz)
Motor Speed	1450 / 1750 min ⁻¹ (50 / 60 Hz)	1450 / 1750 min ⁻¹ (50 / 60 Hz)
Sound Pressure Level	72 dB(A) (50 / 60 Hz)	72 dB(A) (50 / 60 Hz)
Weight approx.	132 / 164 kg (50 / 60 Hz)	193 / 213 kg (50 / 60 Hz)
Dimensions (L x W x H)	685 x 385 x 430 mm	841 x 385 x 430 mm
Inlet / outlet	DN 65 PN 16 / DN 65 PN 16	DN 65 PN 16 / DN 65 PN 16

NEED MORE INFORMATION?

Contact our sales team for technical assistance, product selection, or a customized quotation.

info@zerovakum.com.tr | +90 212 656 29 08 | www.zerovakum.com.tr