



■ DURABLE

- Bolted, robust body construction
- PP / PVDF wetted material options
- 1 mm solids handling

■ COMPACT

- 1.45 kg PP body
- Maximum flow 16 L/min
- 1/4" air inlet


■ VERSATILE

- 1/4" fluid connection
- Wide elastomer selection
- Maximum suction lift 6-7 m


Accessories

- Filter-regulator assembly
- Pulsation dampener
- Air shut-off valve
- Replacement diaphragm and ball kits

Installation / Dimensions



Performance Curve



Technical Data		PP • PVDF
Technical Specification	ZEROVAC Z02	
Model	ZEROVAC Z02	
Maximum flow	16 L/min	
Maximum air pressure	7 bar	
Maximum discharge head	70 m	
Maximum suction lift	6-7 m	
Air consumption	1.8-10 m³/h	
Fluid inlet / outlet	1/4"	
Air inlet	1/4"	
Wetted material options	PP / PVDF	
Elastomer options	Santoprene, Neoprene, Buna-N, EPDM, FKM, PTFE	
Maximum particle size	1 mm	
Fluid temperature	0 ... +82 °C	
PP body weight	1.45 kg	

Note: The performance curve is based on water at ambient temperature. Dimensional tolerance is ±3 mm. Product selection must be based on fluid properties and operating conditions.

FOR MORE INFORMATION

For technical support, product selection or a tailored quotation, please contact our sales team.

info@zerovakum.com.tr
 +90 212 656 29 08
 www.zerovakum.com.tr