


ZEROVAC ZRV 820H27

Two-Stage Blower



■ RELIABLE

- Effective air cooling and long service life
- Nearly maintenance-free, dry and contact-free operation
- Protection against overheating

■ FLEXIBLE

- Robust and lightweight construction
- High pressure and vacuum
- Horizontal and vertical installation

■ QUIET

- Low noise level
- No vibration thanks to precision balancing
- Integrated silencers as standard

Accessories


- Vacuum relief valves
- Additional silencers
- Pressure relief valves
- Inlet filter for vacuum or pressure operation

ZEROVAC ZRV 820H27


Two-Stage Blower




Vacuum Performance Curve



Pressure Performance Curve



Installation Drawing



Technical Data

3 Phase • IP54 • Class F

Model	Hz	kW	Voltage (V)	Current (A)	Air Flow (m³/h)	Vacuum (mbar)	Pressure (mbar)	Noise dB(A)	kg
ZRV 820H27	50	7.5	345-415 /600-690Y	16.7 /9.6Y	520	-400	400	74	83
ZRV 820H27	60	8.6	380-480 /660-720Y	17.3 /10.0Y	620	-360	330	78	83

Note: Performance curves are based on measurements taken with air at 15°C and an atmospheric pressure of 1013 mbar. The total pressure differentials apply at inlet and ambient temperatures up to 25°C.

NEED MORE INFORMATION?

Contact our sales team for technical assistance, product selection, or a customized quotation.

info@zerovakum.com.tr

+90 212 656 29 08

www.zerovakum.com.tr